



LUZHONG 50HP GARDEN TRACTOR MAIN SPECIFICATION

Model		LZ500G	LZ504G	
Type		4 x 2	4 x 4	
Dimensions of Tractor(mm)	Length	2760		
	Width	1120 to 1475		
	Height	1140		
	Tread	Front Wheel	880/960/1080/1130 adjustable	
		Rear Wheel	880-1600 adjustable	
	Axle Base		1650	
Min.Ground Clearance		260		
Structure weight (kg)		1100		
Ballast weight (kg)	Front ballast	56		
	Rear ballast	110		
Rated traction force (N)		7400	9800	
Engine	Model	4100	4100	
	Type	Vertical,4-Cylinder,Water Cooled and 4-stroke		
	Rated Power(kw)	36.8	36.8	
	Rated speed (r/min)	2400		
	Fuel	Diesel		
Tyre	Front Wheel	450-12、450-14(2WD); 600-12(4WD)		
	Rear Wheel	7.5-20、9.5-16、13.6-16		
Clutch		Dual-stage clutch		
Steering		power steering		
Transmission Type		8+2 or (8+2)x2 with creeper shift		
Suspension Type		3-point links		
PTO	Type and Rev	Semi-independent Type 540		
	Spline Size	F35 Rectangle Spline with 6 teeth		

Structure and specification are subject to change without notice.

1. Designed for small farm, orchards, greenhouses and gardens specially, it has low height, narrow track. Rear 4 hweels is optional.
2. Directly connected with 4 cylinder engine, 50 HP.
3. Basic type 8F+2R, and creeper gears 16F+4F is optional.
4. Standard Cat.I 3-point linkage, most farm implements available.



A NEW TRACTOR

FOR THE VEGETABLE GREENHOUSES AND ORCHARDS

