

60-80HP TRACTOR





LUZHONG 60-80HP 2WD & 4WD TRACTOR MAIN SPECIFICATION

Model		LZ600-TB	LZ650-TB	LZ700-TB	LZ604-TB	LZ654-TB	LZ704-TB	LZ804-TB	
Type		2WD Wheeled Type			4WD Wheeled Type				
Dimensions of Tractor(mm)	Length (to front ballast)	3880							
	Width	1830							
	Height (to the exhaust vent)	2130							
	Tread	Front Wheel	1280						
		Rear Wheel	1300 Fixed or 1200~1500 Adjusted						
	Axle Base	2040							
Min.Ground Clearance	400				325				
Structure weight (kg)		1750	1750	1750	2000	2000	2000	2000	
Ballast weight (kg)	Front ballast	140							
	Rear ballast	200							
PTO power at rated speed KW@rpm		39.6	43	46.3	39.6	43	46.3	49.5	
Engine	Model	4105							
	Type	Vertical,4-Cylinder,Water Cooled and 4-stroke							
	Rated Power(kw)	44.1	47.8	51.5	44.1	47.8	51.5	58.8	
	Rated speed (r/min)	2400							
	Fuel	Diesel							
Tyre	Front Wheel	650-16			9.5-20				
	Rear Wheel	14.9-28			14.9-28				
Clutch		Dual-stage clutch							
Steering		power steering							
Transmission Type		12+12 shuttle gearshift							
Suspension Type		3-point links							
PTO	Type and Rev	Semi-independent Type 540/1000							
	Spline Size	F35 Rectangle Spline with 6 teeth							

Structure and specification are subject to change without notice.